SENTRY
SECURE BY DEFINITION

LPS 1175 / ISSUE 8

C5

SECURITY STEEL DOORS

XTREME 3 / C5 (SR3)



CERTIFIED DOORSET

LPS 1175 Issue 8: C5 (SR3).
LPCB reference: 1284d/01.

Leaf / frame	Galvanised steel; anti-jemmy leading edge; bolted frame corners.
Seals	Tubular silicone frame seal.
Hardware	Locks, latches, panic hardware, handles, closers and stays selected within the rated scope.
Threshold	Standard chamfered 2mm stainless-steel profile; alternative cills / thresholds subject to configuration.
Finish	RAL powder coat; marine-grade, textured, metallic and woodgrain options.

STRUCTURAL OPENING LIMITS / mm

Doorset configuration	Width range	Height range
Single leaf / outward	500-1,500	1,500-2,500
Single + over / side panels; outward	800-3,500	1,800-3,500
Double leaf / outward	1,100-2,900	1,500-2,500
Double + over / side panels; outward	1,400-4,900	1,800-3,500

SPECIFICATION SCOPE

Select all hardware, glazing, louvres and panels within the C5 certification scope. The Xtreme range's fire upgrade is published for B3 only; no fire rating is claimed for this C5 sheet.

FOR QUOTATION

Provide opening sizes, handing, wall construction, rated hardware, threshold, finish and any fire / glazing / louvre requirements. Size ranges are structural openings, not clear passage.

Manufacturer example shown. Security applies to the approved complete assembly and installation. Sources: Metador Xtreme datasheet Rev 6; LPCB Red Book p116.

0113 403 5583 enquiries@sentryautomation.co.uk sentryautomation.co.uk