SENTRY
SECURE BY DEFINITION

LPS 1175 / ISSUE 8

D10

SECURITY STEEL DOORS

XTREME 4 / D10 (SR4)



CERTIFIED DOORSET

LPS 1175 Issue 8: D10 (SR4).
LPCB reference: 1284b/01.

Leaf / frame	Galvanised steel; anti-jemmy leading edge; bolted frame corners.
Seals	Tubular silicone frame seal.
Hardware	Locks, latches, panic hardware, handles, closers and stays selected within the rated scope.
Threshold	Standard chamfered 2mm stainless-steel profile; alternative cills / thresholds subject to configuration.
Finish	RAL powder coat; marine-grade, textured, metallic and woodgrain options.

STRUCTURAL OPENING LIMITS / mm

Doorset configuration	Width range	Height range
Single leaf / outward	500-1,284	1,000-2,752
Double leaf / outward	900-2,492	1,000-2,752

SPECIFICATION SCOPE

The published D10 schedule lists outward-opening single and double doorsets. Additional panels, vision openings, louvres or inward opening are not established by this schedule. Confirm any departure against the certification scope.

FOR QUOTATION

Provide opening sizes, handing, wall construction, rated hardware, threshold, finish and any fire / glazing / louvre requirements. Size ranges are structural openings, not clear passage.

Manufacturer example shown. Security applies to the approved complete assembly and installation. Sources: Metador Xtreme datasheet Rev 6; LPCB Red Book p116.

0113 403 5583 enquiries@sentryautomation.co.uk sentryautomation.co.uk