Sentry Automation Ltd

Strong XF

High-speed rapid roll door for interior use

INTERIOR APPLICATIONS | **1.2mm REINFORCED CURTAIN** | **STANDARD INVERTER**



FOR INTENSIVE INTERIOR USE

Robust construction for larger, frequently used internal openings up to 5,000 × 5,000mm.

REINFORCEMENT & ENDLOCKS

Aluminium curtain reinforcement profiles with integrated EndLocks are supplied as standard.

STANDARD FREQUENCY CONTROL

Opening speed between 1.8 and 2.3m/s, depending on dimensions; closing approximately 0.5m/s.

LIGHT CURTAIN AS STANDARD

Integrated safety light curtain to 2,500mm high, with manual opening on power loss.

STANDARD VISION SECTION

A transparent vision section is supplied as standard; insect-netting sections are optional.

The Strong XF is a high-speed rapid roll door for intensive use in larger interior openings. Its 1.2mm reinforced PVC sections with aluminium profiles and integrated EndLocks provide a robust curtain, with a transparent vision section as standard. Side seals support draught exclusion and climate control; removable column covers simplify maintenance.

5,000 × 5,000mm	1.8–2.3m/s*	0.5m/s
Maximum opening / 25m²	Opening speed depends on size	Approximate closing speed

Supply only • Installation • Repairs • Planned servicing

0113 403 5583 enquiries@sentryautomation.co.uk sentryautomation.co.uk

Sentry Automation Ltd

Strong XF / Specification

DIMENSIONS & PERFORMANCE

Maximum width / height	5,000mm / 5,000mm
Maximum area	25m²
Guide side room	170mm
Slip-on drive side room	340 / 425mm*
Drive fitting clearance	440 / 475mm*
Side-guide profile space	145 / 200mm*
Required headroom	430 / 480mm*
Opening / closing speed	1.8–2.3* / 0.5m/s
Frequency control	Standard
Wind load classification	Width-dependent; see below
Product conformity	EN 13241

CONSTRUCTION & MATERIALS

1.2mm polyester-reinforced PVC curtain in horizontal sections with standard aluminium profiles and integrated EndLocks. Electrically driven aluminium roller; no balance springs.

Hot-dip galvanised steel columns with removable front covers and tailored side seals. Aluminium HardEdge bottom beam as standard; flexible, soft-shell FlexEdge optional.

COLOURS, WINDOWS & COVERS

Curtain colours: blue, black, white, grey, red, orange or yellow. Vision section supplied as standard. Other vision / insect-netting sections available, typically between 1,000 and 2,000mm above floor level.

Optional stainless-steel columns; PVC, galvanised steel or stainless-steel top hood; specified RAL colour for hood / PVC cover; specified finishes subject to quotation.

DRIVE & ELECTRICAL

Direct-drive geared electric motor, mounted on the left or right. Frequency control supplied as standard.

1.5kW drive: LNPE~230V / 50Hz / 16AT.
3.0kW drive: 3N~400V / 50Hz / 16AT.
Motor: IP65. Select supply to suit the drive.
Standard control box: IP54 with CEE plug.

CONTROLS & SAFETY

TS971 / TS981 / T100R FU, selected for the application. Open-stop-close operation, seven-segment display, adjustable hold-open time, permanently open / closed settings, service and run modes.

Safety light curtain to 2,500mm high as standard. Geared motor includes built-in roll-off safety. Manual opening in the event of power loss.

SITE & CONNECTION REQUIREMENTS

Flat mounting frame and adequate mounting space required. Confirm precise installation dimensions with the technical drawing.

Provide the correct separately fused CEE socket within 500mm of the control unit. Use the red 400V or blue 230V CEE socket to suit the selected drive. Control box normally on the drive side about 1,500mm above the floor. Confirm circuit protection with the selected configuration.

OPTIONS & ACCESSORIES

Push-button, pull switch, key switch, photocell, radar, induction loop or radio activation; door-to-door interlock.

Stainless-steel IP65 control box with separate power plug; directly wired IP65 box / main switch; traffic lights and orange / red warning beacon.

WIND LOAD RESISTANCE

Maximum EN 12424 rating by width: up to 3,000mm: Class 2; up to 4,000mm: Class 1; up to 5,000mm: Class 0. Confirm the selected configuration.

To quote: send opening dimensions, headroom and side room, site photographs, postcode, wind / draught conditions, power details, curtain finish and activation requirements.

*Depending on configuration. Based on manufacturer literature dated May 2024. Confirm dimensions, speeds, wind exposure, controls, electrical requirements and availability with quotation. Technical changes reserved.

0113 403 5583 enquiries@sentryautomation.co.uk sentryautomation.co.uk